

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

Amendments to the Claims:

Please cancel claim 1, amend claims 2-4 and 11 as follows.
The following listing of claims will replace all prior versions,
and listings, of claims in the application.

Listing of Claims:

Claim 1 (Cancelled).

Claim 2 (Currently Amended). An automotive passenger
restraint and protection apparatus for an automotive vehicle,
having a seatbelt, for restraining an occupant of the automotive
vehicle by the seatbelt to protect the occupant, comprising:

- 5 a motor for retracting and protracting the seatbelt;
 seatbelt attaching state detecting means for detecting
whether the seatbelt is in a state attached to the occupant or in
a state disconnected from the occupant;
 danger degree detecting means for detecting a significant
10 degree of danger of collision of the automotive vehicle; and

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

control means for controlling said motor so as to retract the seatbelt to a limit thereof and then protract the seatbelt to thereby give a predetermined amount of looseness to the seatbelt,

15 wherein said control means controls said motor so as to give a first predetermined amount of looseness to the seatbelt when the significant degree of danger is not detected by said danger degree detecting means while the seatbelt is detected to be in said state attached to the occupant, and controls said motor so as to give a second predetermined amount of looseness to the
20 seatbelt which is smaller than said first predetermined amount of looseness when the significant degree of danger is detected by said danger degree detecting means while the seatbelt is detected to be in said state attached to the occupant, and

25 wherein said danger degree detecting means comprises at least one of vehicle speed detecting means for detecting traveling speed of the automotive vehicle, braking detecting means for detecting stepping-on of a brake pedal of the automotive vehicle, steering angle change rate detecting means for detecting a rate of change in a steering angle of the
30 automotive vehicle, ambient illuminance detecting means for detecting ambient illuminance of the automotive vehicle, and

Appln. No. 10/732,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

raindrop detecting means for detecting raindrops on the
automotive vehicle.

Claim 3 (Currently Amended). An automotive passenger
restraint and protection apparatus as claimed in claim 2, wherein
~~said danger degree detecting means comprises at least one of~~
~~vehicle speed detecting means for detecting traveling speed of~~
5 ~~the automotive vehicle, braking detecting means for detecting~~
~~stepping-on of a brake pedal of the automotive vehicle, steering~~
~~angle change rate detecting means for detecting a rate of change~~
~~in a steering angle of the automotive vehicle, ambient~~
~~illuminance detecting means for detecting ambient illuminance of~~
10 ~~the automotive vehicle, and raindrop detecting means for~~
~~detecting raindrops on the automotive vehicle,~~ said danger degree
detecting means detecting detects the significant degree of
danger if said vehicle speed detecting means detects that the
traveling speed of the automotive vehicle is higher than a
15 predetermined value and at the same time at least one of
conditions is satisfied that the stepping-on of the brake pedal
is detected by said braking detecting means, the steering angle
change rate detecting means detects that the rate of change of
the steering angle exceeds a predetermined value, the ambient

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

20 illuminance detecting means detects that the ambient illuminance of the automotive vehicle is below a predetermined value, and the raindrop detecting means detects the raindrops on the automotive vehicle.

Claim 4 (Currently Amended). An automotive passenger restraint and protection apparatus ~~as claimed in claim 2, for an automotive vehicle, having a seatbelt, for restraining an occupant of the automotive vehicle by the seatbelt to protect the~~
5 occupant, comprising:

a motor for retracting and protracting the seatbelt;
seatbelt attaching state detecting means for detecting whether the seatbelt is in a state attached to the occupant or in a state disconnected from the occupant;

10 danger degree detecting means for detecting a significant degree of danger of collision of the automotive vehicle; and
control means for controlling said motor so as to retract the seatbelt to a limit thereof and then protract the seatbelt to thereby give a predetermined amount of looseness to the seatbelt,

15 wherein said control means controls said motor so as to give a first predetermined amount of looseness to the seatbelt when the significant degree of danger is not detected by said danger

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

degree detecting means while the seatbelt is detected to be in
said state attached to the occupant, and controls said motor so
20 as to give a second predetermined amount of looseness to the
seatbelt which is smaller than said first predetermined amount of
looseness when the significant degree of danger is detected by
said danger degree detecting means while the seatbelt is detected
to be in said state attached to the occupant, and
25 wherein said danger degree detecting means comprises vehicle
speed detecting means for detecting traveling speed of the
automotive vehicle, and braking detecting means for detecting a
stepping-on force of a brake pedal of the automotive vehicle or
stepping-on speed thereof, said control means controlling said
30 motor such that rotational speed of said motor in retracting the
seatbelt is higher as the stepping-on force or the stepping-on
speed detected by said braking detecting means is larger, when
the traveling speed of the automotive vehicle detected by said
vehicle speed detecting means is higher than a predetermined
35 value.

Claim 5 (Original). An automotive passenger restraint and
protection apparatus as claimed in claim 2, wherein said danger
degree detecting means comprises vehicle speed detecting means
for detecting traveling speed of the automotive vehicle, and

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

5 braking detecting means for detecting stepping-on of a brake
pedal of the automotive vehicle, said control means controlling
said motor such that rotational speed of said motor in retracting
the seatbelt is higher as the traveling speed of the automotive
vehicle detected by said vehicle speed detecting means is higher,
10 when the detected traveling speed is higher than a predetermined
value and at the same time the stepping-on of the brake pedal is
detected by said braking detecting means.

Claim 6 (Original). An automotive passenger restraint and
protection apparatus as claimed in claim 2, wherein said danger
degree detecting means comprises vehicle speed detecting means
for detecting traveling speed of the automotive vehicle, and
5 steering angle change rate detecting means for detecting a rate
of change in a steering angle of the automotive vehicle, said
control means controlling said motor such that rotational speed
of said motor in retracting the seatbelt is higher as the rate of
change in the steering angle detected by said steering angle
10 change rate detecting means is larger, when the traveling speed
of the automotive vehicle detected by said vehicle speed
detecting means is higher than a predetermined value.

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

Claim 7 (Original). An automotive passenger restraint and protection apparatus as claimed in claim 2, wherein said danger degree detecting means comprises vehicle speed detecting means for detecting traveling speed of the automotive vehicle, and
5 steering angle change rate detecting means for detecting a rate of change in a steering angle of the automotive vehicle, said control means controlling said motor such that rotational speed of said motor in retracting the seatbelt is higher as the traveling speed of the automotive vehicle detected by said
10 vehicle speed detecting means is higher, when the detected traveling speed is higher than a predetermined value and at the same time the rate of change in the steering angle detected by said steering angle change rate detecting means is larger than a predetermined value.

Claim 8 (Original). An automotive passenger restraint and protection apparatus as claimed in claim 2, wherein said danger degree detecting means comprises vehicle speed detecting means for detecting traveling speed of the automotive vehicle, and
5 ambient illuminance detecting means for detecting ambient illuminance of the automotive vehicle, said control means controlling said motor such that rotational speed of said motor in retracting the seatbelt is higher as the ambient illuminance

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

detected by said ambient illuminance detecting means is smaller,
10 when the traveling speed of the automotive vehicle detected by
said vehicle speed detecting means is higher than a predetermined
value.

Claim 9 (Original). An automotive passenger restraint and
protection apparatus as claimed in claim 2, wherein said danger
degree detecting means comprises vehicle speed detecting means
for detecting traveling speed of the automotive vehicle, and
5 ambient illuminance detecting means for detecting ambient
illuminance of the automotive vehicle, said control means
controlling said motor such that rotational speed of said motor
in retracting the seatbelt is higher as the traveling speed of
the automotive vehicle detected by said vehicle speed detecting
10 means is higher, when the detected traveling speed is higher than
a predetermined value and at the same time the ambient
illuminance detected by said ambient illuminance detecting means
is smaller than a predetermined value.

Claim 10 (Original). An automotive passenger restraint and
protection apparatus as claimed in claim 2, wherein said danger
degree detecting means comprises vehicle speed detecting means
for detecting traveling speed of the automotive vehicle, and

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

5 raindrop detecting means for detecting raindrop on the automotive
vehicle, said control means controlling said motor such that
rotational speed of said motor in retracting the seatbelt is
higher as the traveling speed of the automotive vehicle detected
by said vehicle speed detecting means is higher, when the
10 detected traveling speed is higher than a predetermined value and
at the same time the raindrops are detected by said raindrop
detecting means.

Claim 11 (Currently Amended). An automotive passenger
restraint and protection apparatus ~~as claimed in claim 2,~~ for an
automotive vehicle, having a seatbelt, for restraining an
occupant of the automotive vehicle by the seatbelt to protect the
5 occupant, comprising:

a motor for retracting and protracting the seatbelt;
seatbelt attaching state detecting means for detecting
whether the seatbelt is in a state attached to the occupant or in
a state disconnected from the occupant;
10 danger degree detecting means for detecting a significant
degree of danger of collision of the automotive vehicle; and
control means for controlling said motor so as to retract
the seatbelt to a limit thereof and then protract the seatbelt to
thereby give a predetermined amount of looseness to the seatbelt,

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

- 15 wherein said control means controls said motor so as to give
a first predetermined amount of looseness to the seatbelt when
the significant degree of danger is not detected by said danger
degree detecting means while the seatbelt is detected to be in
said state attached to the occupant, and controls said motor so
20 as to give a second predetermined amount of looseness to the
seatbelt which is smaller than said first predetermined amount of
looseness when the significant degree of danger is detected by
said danger degree detecting means while the seatbelt is detected
to be in said state attached to the occupant, and
25 wherein said danger degree detecting means comprises vehicle
speed detecting means for detecting traveling speed of the
automotive vehicle, and braking detecting means for detecting a
stepping-on force of a brake pedal of the automotive vehicle or
stepping-on speed thereof, said control means controlling said
30 motor such that an amount of protraction of the seatbelt is
smaller as the stepping-on force or the stepping-on speed
detected by said braking detecting means is larger, when the
traveling speed of the automotive vehicle detected by said
vehicle speed detecting means is higher than a predetermined
35 value.

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

Claim 12 (Original). An automotive passenger restraint and protection apparatus as claimed in claim 2, wherein said danger degree detecting means comprises vehicle speed detecting means for detecting traveling speed of the automotive vehicle, and
5 braking detecting means for detecting stepping-on of a brake pedal of the automotive vehicle, said control means controlling said motor such that an amount of protraction of the seatbelt is smaller as the traveling speed of the automotive vehicle detected by said vehicle speed detecting means is higher, when the
10 detected traveling speed is higher than a predetermined value and at the same time the stepping-on of the brake pedal is detected by said braking detecting means.

Claim 13 (Original). An automotive passenger restraint and protection apparatus as claimed in claim 2, wherein said danger degree detecting means comprises vehicle speed detecting means for detecting traveling speed of the automotive vehicle, and
5 steering angle change rate detecting means for detecting a rate of change in a steering angle of the automotive vehicle, said control means controlling said motor such that an amount of protraction of the seatbelt is smaller as the rate of change in the steering angle detected by said steering angle change rate
10 detecting means is larger, when the traveling speed of the

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

automotive vehicle detected by said vehicle speed detecting means is higher than a predetermined value.

Claim 14 (Original). An automotive passenger restraint and protection apparatus as claimed in claim 2, wherein said danger degree detecting means comprises vehicle speed detecting means for detecting traveling speed of the automotive vehicle, and
5 steering angle change rate detecting means for detecting a rate of change in a steering angle of the automotive vehicle, said control means controlling said motor such that an amount of protraction of the seatbelt is smaller as the traveling speed of the automotive vehicle detected by said vehicle speed detecting
10 means is higher, when the detected traveling speed is higher than a predetermined value and at the same time the rate of change in the steering angle detected by said steering angle change rate detecting means is larger than a predetermined value.

Claim 15 (Original). An automotive passenger restraint and protection apparatus as claimed in claim 2, wherein said danger degree detecting means comprises vehicle speed detecting means for detecting traveling speed of the automotive vehicle, and
5 ambient illuminance detecting means for detecting ambient illuminance of the automotive vehicle, said control means

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

controlling said motor such that an amount of protraction of the
seatbelt is smaller as the ambient illuminance detected by the
ambient illuminance detecting means is smaller, when the
10 traveling speed of the automotive vehicle detected by said
vehicle speed detecting means is higher than a predetermined
value.

Claim 16 (Original). An automotive passenger restraint and
protection apparatus as claimed in claim 2, wherein said danger
degree detecting means comprises vehicle speed detecting means
for detecting traveling speed of the automotive vehicle, and
5 ambient illuminance detecting means for detecting ambient
illuminance of the automotive vehicle, said control means
controlling said motor such that an amount of protraction of the
seatbelt is smaller as the traveling speed of the automotive
vehicle detected by said vehicle speed detecting means is higher,
10 when the detected traveling speed is higher than a predetermined
value and at the same time the ambient illuminance detected by
the ambient illuminance detecting means is smaller than a
predetermined value.

Claim 17 (Original). An automotive passenger restraint and
protection apparatus as claimed in claim 2, wherein said danger

Appln. No. 10/722,943
Amendment dated March 17, 2005
Reply to Office Action of January 14, 2005

degree detecting means comprises vehicle speed detecting means
for detecting traveling speed of the automotive vehicle, and
5 raindrop detecting means for detecting raindrops on the
automotive vehicle, said control means controlling said motor
such that an amount of protraction of the seatbelt is smaller as
the traveling speed of the automotive vehicle detected by said
vehicle speed detecting means is higher, when the detected
10 traveling speed is higher than a predetermined value and at the
same time the raindrops are detected by said raindrop detecting
means.